

## RESISTENZE PER UGELLO TENUTA STAGNA IN OTTONE

(Misure standard)



In caso si avessero necessità differenti in termini di misure e potenze, si prega di contattare gli uffici.

DIAMETRO (mm)	LUNGHEZZA (mm)	POTENZA (Watt/230 Volt)
25	20	80
25	25	85
25	30	100
25	35	125
30	20	100
30	25	105
30	30	125
30	30	160
30	35	145
30	40	165
30	50	235
32	38	195
35	20	110
35	25	120
35	30	145
35	35	170
35	40	195
35	45	220
35	60	325
38	20	110
38	25	140
38	30	165
38	35	200
38	38	215
38	40	175
38	40	220
38	45	250
38	50	300
40	20	110
40	25	140

40	30	165
40	35	195
40	40	225
40	45	250
40	50	275
40	60	305
42	20	120
42	25	145
42	30	175
42	35	205
42	40	235
45	20	130
45	25	155
45	30	190
45	35	220
45	40	250
45	45	285
45	50	315
45	55	345
48	20	135
48	30	200
48	50	380
50	20	140
50	25	175
50	30	210
50	35	245
50	40	280
50	50	350
50	60	420
55	20	155
55	25	190
55	30	230
55	35	270
55	40	310
55	50	385
60	20	165
60	25	210
60	30	250
60	35	295
60	40	335
60	50	420
60	60	505
65	20	180
65	25	225
65	30	275
65	35	320

65	40	365
65	50	455
65	60	550
70	20	195
70	25	245
70	30	295
70	35	345
70	40	395
70	50	490
70	60	590
75	20	210
75	25	260
75	30	315
75	35	370
75	40	420
75	50	525
75	60	635
80	20	225
80	25	280
80	30	335
80	35	395
80	40	450
80	50	565
80	60	675
85	20	240
85	25	300
85	30	360
85	35	420
85	40	480
85	50	600
85	60	720
90	20	250
90	25	315
90	30	380
90	35	445
90	40	505
90	50	635
90	60	760
95	20	265
95	25	335
95	30	400
95	35	465
95	40	535
95	50	670
95	60	800
100	20	280

100	25	350
100	30	420
100	35	490
100	40	560
100	50	700
100	60	840

## RESISTENZE PER UGELLO TENUTA STAGNA IN ACCIAIO

(Misure standard)



In caso si avessero necessità differenti in termini di misure e potenze, si prega di contattare gli uffici.

DIAMETRO (mm)	LARGHEZZA (mm)	POTENZA (Watt/230 Volt)
25	30	130
30	25	130
30	30	170
30	35	200
30	40	230
35	25	160
35	30	200
35	35	240
35	40	270
35	45	310
40	25	190
40	30	230
40	35	270
40	40	310
40	45	350
42	25	200

42	30	240
42	35	290
42	40	330
45	25	210
45	30	260
45	35	310
45	40	350
45	45	400
45	50	450
45	55	490
50	20	190
50	25	240
50	30	290
50	35	340
50	40	390
50	50	500
50	60	600
55	20	210
55	25	270
55	30	320
55	35	380
55	40	430
55	50	540
60	20	230
60	25	290
60	30	350
60	35	410
60	40	470
60	50	600
60	60	720
65	20	250
65	25	320
65	30	380
65	35	450
65	40	520
65	50	650
70	20	270
70	25	340
70	30	410
70	35	490
70	40	560
70	50	700
70	60	840
75	20	290
75	25	370
75	30	440

75	35	520
75	40	560
75	50	750
75	60	900
80	20	310
80	25	390
80	30	470
80	35	560
80	40	640
80	50	800
80	60	960
85	20	330
85	25	420
85	30	500
85	35	590
85	40	680
85	50	850
85	60	1020
90	20	350
90	25	440
90	30	540
90	35	630
90	40	720
90	50	900
90	60	1080
95	20	370
95	25	470
95	30	570
95	35	660
95	40	760
95	50	950
95	60	1150
100	20	380
100	25	500
100	30	600
100	35	700
100	40	800
100	50	1000
100	60	1200

## RESISTENZE PER UGELLO DUE CAVI

(Misure standard)



In caso si avessero necessità differenti in termini di misure e potenze, si prega di contattare gli uffici.

DIAMETRO (mm)	LARGHEZZA(mm)	POTENZA(Watt/230 Volt)
25	30	90
30	25	120
30	30	140
30	35	165
30	40	185
35	25	135
35	30	165
35	35	190
35	40	220
35	45	235
40	25	155
40	30	190
40	35	220
40	40	250
40	45	280
42	25	165
42	30	200
42	35	230
42	40	265
45	25	175
45	30	210
45	35	250
45	40	280

45	45	320
45	50	350
50	20	155
50	25	195
50	30	235
50	35	275
50	40	315
50	50	390
55	20	170
55	25	215
55	30	260
55	35	260
55	40	345
55	50	430
60	20	190
60	25	235
60	30	280
60	35	330
60	40	375
60	50	470
60	60	565
65	20	200
65	25	255
65	30	305
65	35	355
65	40	405
65	50	510
65	60	610
70	20	220
70	25	270
70	30	330
70	35	380
70	40	440
70	50	550
70	60	660
75	20	235
75	25	295
75	30	355
75	35	410
75	40	470
75	50	590
75	60	705
80	20	250
80	25	310
80	30	375
80	35	440



80	40	440
80	50	500
80	60	750
85	20	265
85	25	330
85	30	400
85	35	465
85	40	530
85	50	665
85	60	800
90	20	280
90	25	350
90	30	420
90	35	490
90	40	565
90	50	705
90	60	845
95	20	300
95	25	370
95	30	445
95	35	520
95	40	595
95	50	745
95	60	895
100	20	315
100	25	390
100	30	470
100	35	550
100	40	630
100	50	785
100	60	940